

# WARRANTY CERTIFICATE

## PERFORMANCE WARRANTY – SOUNDLEVEL®

Elastomeric Liquid Acoustical Underlayment & 90% RH Moisture Vapor Barrier

W.F. Taylor LLC (herein Taylor) provides a 10-year limited warranty when Soundlevel® is used for interior sound and/or moisture control (see current technical data sheet for complete details). Soundlevel® shall be free from manufacturing defect and will perform as designed when properly used.

Soundlevel® is a sound mitigation system which affects IIC (Impact Isolation Class) & STC (Sound Transmission Class) through the substrate, as well as controls concrete substrate moisture vapor up to 90% RH and 10 lbs MVER, with no need for pH testing. Substrates shall be properly prepared per ASTM F710, have no visible or standing moisture, have an intact moisture vapor retarder per ASTM E1745, and be without hydrostatic pressure. When used as part of a glue-down application system, Soundlevel® is warranted solely with the use of a recommended Taylor adhesive. When used as a concrete moisture vapor barrier, the substrate must also be properly prepared and porous per ASTM F3191. The installation must be performed following both the flooring manufacturer's and Taylor's guidelines. For the latest product information and application instructions please visit [www.tayloradhesives.com](http://www.tayloradhesives.com).

If an installation failure occurs as a direct result of the use of defective Soundlevel®, Taylor will pay for equivalent floor covering, replacement Taylor adhesive & Soundlevel®, and for reasonable labor costs to repair or replace the failed portion of the installation as determined by Taylor at its sole discretion. This warranty applies only to Soundlevel® related bond failures. Taylor cannot warrant those variables over which it has no control such as the quantity of Soundlevel® used, the workmanship of the installer, the condition of the subfloor, excessive moisture, the stability of the flooring product and its suitability for installation on the affected job-site, or any other conditions that might affect the installation.

Taylor reserves the right as deemed necessary to inspect any claim for cause or this warranty is null and void. Any repairs done prior to inspection by a Taylor representative voids any warranty. This warranty is non-transferable.

**Phone:** 800.868.4583 **Fax:** 706.712.0909  
**Address:** 800 College Drive, Dalton, GA 30720

 **TAYLOR**<sup>™</sup>  
TaylorAdhesives.com